

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 15225089 |
| Valid tyre size | VF 520 / 80 R 26 CFO |
| LI / SI / PR | 168 A8 |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 372 + |



Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

Technical Informations

| | |
|------------------------------|----------------------|
| Item number | 15225089 |
| EAN | 7291050084949 |
| Valid tyre size | VF 520 / 80 R 26 CFO |
| LI / SI / PR | 168 A8 |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 372 + |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 148,70 |
| Recommended rim size | DW16L |
| Permitted rim size | DW18L |
| Maximum air pressure [bar]. | 2,80 |
| Section width (mm) | 505 |
| Outer diameter of tyre [mm]. | 1465 |
| Stat. radius (SLR) [mm] | 627 |
| Rolling circumference [mm]. | 4335 |
| Tread depth (mm) | 45,5 |
| Number of lugs | 18x2 |
| Tyre capacity 75% [ltr.] | 342.75 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 168 A8 | 5600 | 40 | | 2,80 | |