

## **TYRES**

Product group	Tyres	
Item number	15225089	
Valid tyre size	VF 520 / 80 R 26 CFO	
LI / SI / PR	168 A8	
TL/TT	TL Alliance Agriflex 372 +	
Brand		
Tread pattern		





## Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.



## **Technical Informations**

Item number	15225089
EAN	7291050084949
Valid tyre size	VF 520 / 80 R 26 CFO
LI / SI / PR	168 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	148,70
Recommended rim size	DW16L
Permitted rim size	DW18L
Maximum air pressure [bar].	2,80
Section width (mm)	505
Outer diameter of tyre [mm].	1465
Stat. radius (SLR) [mm]	627
Rolling circumference [mm].	4335
Tread depth (mm)	45,5
Number of lugs	18x2
Tyre capacity 75% [ltr.]	342.75
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		2,80	