

TYRES

Product group	Tyres	
Item number	15225173	
Valid tyre size	520 / 70 R 34	
LI / SI / PR	168 A8 / 165 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	370	



Notes and features

- Agricultural wide-base tyre of the 70 series for tractors in the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for improved traction and high mileage.



Technical Informations

Item number	15225173
EAN	7291050021913
Valid tyre size	520 / 70 R 34
LI / SI / PR	168 A8 / 165 B
TL/TT	TL
Brand	Alliance
Tread pattern	370
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	160,68
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	4,40
Section width (mm)	516
Outer diameter of tyre [mm].	1632
Stat. radius (SLR) [mm]	739
Rolling circumference [mm].	4826
Tread depth (mm)	54,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	375
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		4,40	
165 B	5150	50		4,40	