

## **TYRES**

Product group	Tyres
Item number	15225180
Valid tyre size	710 / 60 R 34
LI / SI / PR	167 A8 / 164 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 378 XL





## Notes and features

- Super volume tyre for high-performance tractors from approx. 200 hp and harvesters.
- Designed for versatile applications.
- Comfortable on-road handling and high traction combined with very good self-cleaning properties in field operations.
- Built-in steel belts for extra stability, protection against punctures and large contact area.
- Innovative rubber compound for a longer service life and flexible sidewalls (for air pressure adjustment).



## **Technical Informations**

Item number	15225180
EAN	7291050066051
Valid tyre size	710 / 60 R 34
LI / SI / PR	167 A8 / 164 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 378 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	212,00
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	710
Outer diameter of tyre [mm].	1712
Stat. radius (SLR) [mm]	771
Rolling circumference [mm].	5128
Tread depth (mm)	56,7
Number of lugs	20x2
Tyre capacity 75% [ltr.]	617
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		2,40	
164 D	5000	65		2,40	