

TYRES

Product group	Tyres
Item number	15225252
Valid tyre size	IF 800 / 70 R 38 CFO
LI / SI / PR	187 A8 / 183 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372



 **ALLIANCE**

Notes and features

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

Technical Informations

Item number	15225252
EAN	7291050066785
Valid tyre size	IF 800 / 70 R 38 CFO
LI / SI / PR	187 A8 / 183 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	393,49
Recommended rim size	27
Permitted rim size	25
Maximum air pressure [bar].	2,80
Section width (mm)	826
Outer diameter of tyre [mm].	2083
Stat. radius (SLR) [mm]	928
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6214
Tread depth (mm)	63,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1121
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
187 A8	9750	40		2,80	
183 B	8750	50		2,80	