

TYRES

Product group	Tyres
Item number	15225286
Valid tyre size	620 / 75 R 34
LI / SI / PR	170 A8 / 170 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

Technical Informations

Item number	15225286
EAN	7291050056496
Valid tyre size	620 / 75 R 34
LI / SI / PR	170 A8 / 170 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	236,97
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	3,20
Section width (mm)	610
Outer diameter of tyre [mm].	1820
Stat. radius (SLR) [mm]	828
Rolling circumference [mm].	5435
Tread depth (mm)	53,0
Tyre capacity 75% [ltr.]	624
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A8	6000	40		3,20	
170 B	6000	50		3,20	