

TYRES

| Product group | Tyres | |
|-----------------|------------------|--|
| Item number | 15226060 | |
| Valid tyre size | VF 380 / 85 R 30 | |
| LI / SI / PR | 146 D | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | Agriflex 354 + | |



Notes and features

- The Alliance Agriflex 354 is a row crop tyre with VF technology for tractors, self-propelled and towed field sprayers.
- As a VF tyre, it has 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belted construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.



Technical Informations

| Item number | 15226060 |
|------------------------------|------------------|
| EAN | 7291050082419 |
| Valid tyre size | VF 380 / 85 R 30 |
| LI / SI / PR | 146 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 354 + |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 95,50 |
| Recommended rim size | 13 |
| Permitted rim size | 12 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 394 |
| Outer diameter of tyre [mm]. | 1412 |
| Stat. radius (SLR) [mm] | 634 |
| Rolling circumference [mm]. | 4163 |
| Tread depth (mm) | 47,0 |
| Number of lugs | 23x2 |
| Tyre capacity 75% [ltr.] | 214.5 |
| Guarantee period | 10 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 146 D | 3000 | 65 | | 1,60 | |