

TYRES

Product group	Tyres
Item number	15226680
Valid tyre size	300 / 95 R 52
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**

Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226680
EAN	7291050016711
Valid tyre size	300 / 95 R 52
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	91,00
Recommended rim size	10
Permitted rim size	8, 9
Maximum air pressure [bar].	3,60
Section width (mm)	318
Outer diameter of tyre [mm].	1891
Stat. radius (SLR) [mm]	887
Rolling circumference [mm].	5781
Tread depth (mm)	37,0
Number of lugs	33x2
Lug width (mm)	26
Tyre capacity 75% [ltr.]	216.75
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,60	
148 D	3150	65		3,60	