

TYRES

Product group	Tyres
Item number	15226680
Valid tyre size	300 / 95 R 52
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



Technical Informations

Item number	15226680
EAN	7291050016711
Valid tyre size	300 / 95 R 52
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	91,00
Recommended rim size	10
Permitted rim size	8, 9
Maximum air pressure [bar].	3,60
Section width (mm)	318
Outer diameter of tyre [mm].	1891
Stat. radius (SLR) [mm]	887
Rolling circumference [mm].	5781
Tread depth (mm)	37,0
Number of lugs	33x2
Lug width (mm)	26
Tyre capacity 75% [ltr.]	216.75
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,60	
148 D	3150	65		3,60	