

TYRES

Product group	Tyres
Item number	15226700
Valid tyre size	270 / 95 R 54
LI / SI / PR	149 A8 / 146 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**

Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226700
EAN	7291050043748
Valid tyre size	270 / 95 R 54
Alternative size 1	11.2R54
LI / SI / PR	149 A8 / 146 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,99
Recommended rim size	10
Permitted rim size	8, 9
Maximum air pressure [bar].	3,60
Section width (mm)	285
Outer diameter of tyre [mm].	1900
Stat. radius (SLR) [mm]	901
Rolling circumference [mm].	5826
Tread depth (mm)	36,0
Number of lugs	33x2
Lug width (mm)	26
Tyre capacity 75% [ltr.]	167.25
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		3,60	
146 D	3000	65		3,60	