

TYRES

Product group	Tyres
Item number	15226704
Valid tyre size	IF 270 / 105 R 54
LI / SI / PR	158 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354



Notes and features

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, self-propelled and towed field sprayers.
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

Technical Informations

Item number	15226704
EAN	7291050073028
Valid tyre size	IF 270 / 105 R 54
LI / SI / PR	158 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	107,60
Recommended rim size	9
Maximum air pressure [bar].	4,40
Section width (mm)	280
Outer diameter of tyre [mm].	1946
Stat. radius (SLR) [mm]	917
Rolling circumference [mm].	5949
Tread depth (mm)	46,0
Number of lugs	37x2
Tyre capacity 75% [ltr.]	154.8
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		4,40	