

## **TYRES**

Product group	Tyres
Item number	15226744
Valid tyre size	620 / 75 R 26
LI / SI / PR	167 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	360



## Notes and features

- Universal agricultural wide-base tyre for tractors, harvesters and other farm machinery.
- High air volume for increased load capacity and low ground pressure.
- Adapted lugs for massive traction and very good ride comfort at the same time.
- Strong radial casing with reinforced bead and sidewall for a long service life.



## **Technical Informations**

Item number	15226744
EAN	8903635010722
Valid tyre size	620 / 75 R 26
Alternative size 1	23.1R26
LI / SI / PR	167 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	360
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	166,85
Recommended rim size	DW20B
Maximum air pressure [bar].	3,20
Section width (mm)	605
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	730
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4685
Tread depth (mm)	46,5
Tyre capacity 75% [ltr.]	493
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		3,20	
164 B	5000	50		3,20	