

## **TYRES**

Product group	Tyres	
Item number	15226762	
Valid tyre size	680 / 85 R 32	
LI / SI / PR	178 A8	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multistar 376	





## Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.



## **Technical Informations**

Item number	15226762
EAN	7291050066297
Valid tyre size	680 / 85 R 32
LI / SI / PR	178 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	279,82
Recommended rim size	21
Maximum air pressure [bar].	3,20
Section width (mm)	660
Outer diameter of tyre [mm].	1960
Stat. radius (SLR) [mm]	884
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5815
Tread depth (mm)	50,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	835
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Ind	lex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178	A8	7500	40		3,20	