

TYRES

Product group	Tyres
Item number	15226833
Valid tyre size	900 / 50 R 42
LI / SI / PR	168 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 378 XL





Notes and features

- Super volume tyre for high-performance tractors from approx. 200 hp and harvesters.
- Designed for versatile applications.
- Comfortable on-road handling and high traction combined with very good self-cleaning properties in field operations.
- Built-in steel belts for extra stability, protection against punctures and large contact area.
- Innovative rubber compound for a longer service life and flexible sidewalls (for air pressure adjustment).



Technical Informations

Item number	15226833
EAN	7291050065849
Valid tyre size	900 / 50 R 42
LI / SI / PR	168 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 378 XL
Carcass properties	Stubble Guard
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	289,63
Recommended rim size	DW28B
Permitted rim size	DW27B, DW30B
Maximum air pressure [bar].	1,60
Section width (mm)	855
Outer diameter of tyre [mm].	1947
Stat. radius (SLR) [mm]	860
Rolling circumference [mm].	5771
Tread depth (mm)	57,0
Tyre capacity 75% [ltr.]	1000.5
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		1,60	