

TYRES

Product group	Tyres	
Item number	15226835	
Valid tyre size	900 / 60 R 42	
LI / SI / PR	180 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agristar 378 XL	





Notes and features

- Super volume tyre for high-performance tractors from approx. 200 hp and harvesters.
- Designed for versatile applications.
- Comfortable on-road handling and high traction combined with very good self-cleaning properties in field operations.
- Built-in steel belts for extra stability, protection against punctures and large contact area.
- Innovative rubber compound for a longer service life and flexible sidewalls (for air pressure adjustment).



Technical Informations

Item number	15226835
EAN	7291050065986
Valid tyre size	900 / 60 R 42
LI / SI / PR	180 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 378 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	368,54
Recommended rim size	28
Permitted rim size	27, 30
Maximum air pressure [bar].	2,40
Section width (mm)	890
Outer diameter of tyre [mm].	2140
Stat. radius (SLR) [mm]	951
Rolling circumference [mm].	6356
Tread depth (mm)	63,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1249.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Ind	lex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180) D	8000	65		2,40	