

## **TYRES**

Product group	Tyres
Item number	15227080
Valid tyre size	16.9 R 26
LI / SI / PR	135 A8 / 132 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



## Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.

- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.



## **Technical Informations**

Item number	15227080
EAN	7291050017664
Valid tyre size	16.9 R 26
LI / SI / PR	135 A8 / 132 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	86,18
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	429
Outer diameter of tyre [mm].	1370
Stat. radius (SLR) [mm]	609
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4068
Tread depth (mm)	45,5
Number of lugs	19x2
Lug width (mm)	35
Tyre capacity 75% [ltr.]	250.5
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40		1,60	
132 B	2000	50		1,60	