

## **TYRES**

·		
Product group	Tyres	
Item number	15227205	
Valid tyre size	12.4 R 32	
LI / SI / PR	142 A8 / 139 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Power Drive 356	



## Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.

- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.



## **Technical Informations**

Item number	15227205
EAN	7291050044257
Valid tyre size	12.4 R 32
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	69,45
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	4,20
Section width (mm)	315
Outer diameter of tyre [mm].	1350
Stat. radius (SLR) [mm]	627
Rolling circumference [mm].	4055
Tyre capacity 75% [ltr.]	144
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		4,20	
139 B	2430	50		4,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.