

TYRES

Product group	Tyres	
Item number	15227383	
Valid tyre size	18.4 R 42	
LI / SI / PR	169 A8 / 166 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Power Drive 356	



Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.

- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.



Technical Informations

Item number	15227383
EAN	7291050050302
Valid tyre size	18.4 R 42
LI / SI / PR	169 A8 / 166 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	187,50
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	4,50
Section width (mm)	467
Outer diameter of tyre [mm].	1850
Stat. radius (SLR) [mm]	853
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5638
Tread depth (mm)	45,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	439.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		4,50	
166 B	5300	50		4,50	