

## TYRES

Product group	Tyres
Item number	15227412
Valid tyre size	420 / 80 R 46
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	385



## Notes and features

- Agricultural radial tyre of the 80/85 series for high-performance tractors up to approx. 200 hp.
- High air volume for enormous load capacity and excellent ride comfort.
- R-1W tread pattern (20% higher tread depth compared with R-1) in conjunction with optimum number of lugs for good traction and self-cleaning.
- Reinforced bead and lugs for a long service life.
- Stubble guard rubber compound provides protection against punctures caused by e.g. corn stubble.

## Technical Informations

Item number	15227412
EAN	7291050057721
Valid tyre size	420 / 80 R 46
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	385
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	153,02
Recommended rim size	13
Permitted rim size	12, 14
Maximum air pressure [bar].	3,20
Section width (mm)	420
Outer diameter of tyre [mm].	1861
Stat. radius (SLR) [mm]	859
Rolling circumference [mm].	5611
Tyre capacity 75% [ltr.]	321
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		3,20	
159 D	4375	65		3,20	