Bohnenkamp Moving Professionals

10.05.2025

TYRES

Product group	Tyres
Item number	15227598
Valid tyre size	420 / 85 R 26
LI / SI / PR	135 A8 / 135 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II



≈Alliance

Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15227598
EAN	8903635027454
Valid tyre size	420 / 85 R 26
Alternative size 1	16.9R26
LI / SI / PR	135 A8 / 135 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	91,30
Recommended rim size	W15L
Permitted rim size	W14L
Maximum air pressure [bar].	1,60
Section width (mm)	429
Outer diameter of tyre [mm].	1370
Stat. radius (SLR) [mm]	626
Rolling circumference [mm].	4072
Tread depth (mm)	48,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	225
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40		1,60	
135 B	2180	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.