

TYRES

|                 |                 |
|-----------------|-----------------|
| Product group   | Tyres           |
| Item number     | 15235255        |
| Valid tyre size | 500 / 85 R 30   |
| LI / SI / PR    | 170 A8 / 176 A8 |
| TL/TT           | TL              |
| Brand           | Alliance        |
| Tread pattern   | 570             |



Notes and features

- Radial multipurpose tyre for a wide variety of applications.
  - Specially suited for use on harvesters.
  - Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
  - Radial textile casing with steel belt reinforcement.

## Technical Informations

|                              |                 |
|------------------------------|-----------------|
| Item number                  | 15235255        |
| EAN                          | 7291050061032   |
| Valid tyre size              | 500 / 85 R 30   |
| LI / SI / PR                 | 170 A8 / 176 A8 |
| TL/TT                        | TL              |
| Brand                        | Alliance        |
| Tread pattern                | 570             |
| Carcass properties           | Steel Belted    |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 106         |
| Nettogewicht [kg] (gültig)   | 154,57          |
| Recommended rim size         | 16              |
| Permitted rim size           | 15              |
| Maximum air pressure [bar].  | 2,80            |
| Section width (mm)           | 505             |
| Outer diameter of tyre [mm]. | 1602            |
| Stat. radius (SLR) [mm]      | 698             |
| Rolling circumference [mm].  | 4802            |
| Tread depth (mm)             | 39,0            |
| Guarantee period             | 10 years        |
| E-Ready                      | No              |

Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 170 A8 | 6000               | 40           | Drive Wheel   | 2,80                     |              |
| 176 A8 | 7100               | 40           | Free Rolling  | 2,80                     |              |