

TYRES

Product group	Tyres
Item number	15235260
Valid tyre size	620 / 70 R 30
LI / SI / PR	166 A8 / 178 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570



Notes and features

- Radial multipurpose tyre for a wide variety of applications.
 - Specially suited for use on harvesters.
 - Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
 - Radial textile casing with steel belt reinforcement.

Technical Informations

Item number	15235260
EAN	7291050061445
Valid tyre size	620 / 70 R 30
LI / SI / PR	166 A8 / 178 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	173,19
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,50
Section width (mm)	608
Outer diameter of tyre [mm].	1622
Stat. radius (SLR) [mm]	727
Rolling circumference [mm].	4835
Tread depth (mm)	47,0
Tyre capacity 75% [ltr.]	666
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40	Drive Wheel	2,50	
178 A8	7500	40	Free Rolling	2,50	