Bohnenkamp Moving Professionals

09.05.2025

TYRES

Product group	Tyres
Item number	15284020
Valid tyre size	305 / 70 R 16.5
LI / SI / PR	141 A5
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550



Notes and features

- Municipal tyres for varied use, e.g. for tractors in • contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread • pattern.
- Low rolling resistance ensures high fuel savings . compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and • protection against punctures.
- With M+S identification.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15284020
EAN	7291050060066
Valid tyre size	305 / 70 R 16.5
Alternative size 1	12R16.5
LI / SI / PR	141 A5
TL/TT	ΤL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	42,67
Recommended rim size	9.75
Maximum air pressure [bar].	4,00
Section width (mm)	304
Outer diameter of tyre [mm].	832
Stat. radius (SLR) [mm]	374
Rolling circumference [mm].	2469
Tread depth (mm)	23,7
Tyre capacity 75% [ltr.]	59
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A5	2575	25		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.