

TYRES

Product group	Tyres	
Item number	15284051	
Valid tyre size	500 / 70 R 24	
LI / SI / PR	164 A8 / 164 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multiuse 550	



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.



Technical Informations

Item number	15284051
EAN	7291050060387
Valid tyre size	500 / 70 R 24
Alternative size 1	19.5LR24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	117,04
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	4,00
Section width (mm)	504
Outer diameter of tyre [mm].	1303
Stat. radius (SLR) [mm]	601
Rolling circumference [mm].	3929
Tread depth (mm)	28,8
Tyre capacity 75% [ltr.]	278
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	