

## TYRES

Product group	Tyres
Item number	15284090
Valid tyre size	480 / 65 R 28
LI / SI / PR	154 A8 / 149 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550



## Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

## Technical Informations

Item number	15284090
EAN	7291050057202
Valid tyre size	480 / 65 R 28
LI / SI / PR	154 A8 / 149 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	114,79
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	3,20
Section width (mm)	475
Outer diameter of tyre [mm].	1336
Stat. radius (SLR) [mm]	607
Rolling circumference [mm].	4020
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	249
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40		3,20	
149 D	3250	65		3,20	