

TYRES

| Product group | Tyres | |
|-----------------|---------------------------|--|
| Item number | 15284320 | |
| Valid tyre size | 540 / 65 R 30 | |
| LI / SI / PR | 161 A8 / 156 D | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | Multiuse Professional 551 | |



Notes and features

- The Alliance Multiuse Professional 551 is a new and recently developed tyre for use on municipal tractors, backhoe loaders and other agro-industrial machinery.
- Its additional sipes on the tread blocks ensure optimum handling, ride comfort and traction on dry, wet and snowcovered surfaces.
- The tyre is marked M+S and specially equipped for winter use
- Due to the unique combination of special rubber compound and tread pattern design, the tyre guarantees excellent performance and a long service life.
- The strong steel-belted casing provides damage protection and optimum stability.



Technical Informations

| Item number | 15284320 |
|------------------------------|---------------------------|
| EAN | 7291050083126 |
| Valid tyre size | 540 / 65 R 30 |
| LI / SI / PR | 161 A8 / 156 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Multiuse Professional 551 |
| M+S | M+S |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 143,60 |
| Recommended rim size | DW18L |
| Permitted rim size | DW16L |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 544 |
| Outer diameter of tyre [mm]. | 1465 |
| Stat. radius (SLR) [mm] | 674 |
| Rolling circumference [mm]. | 4413 |
| Tread depth (mm) | 28,0 |
| Number of lugs | 42x2 |
| Tyre capacity 75% [ltr.] | 366 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 161 A8 | 4625 | 40 | | 3,20 | |
| 156 D | 4000 | 65 | | 3,20 | |