

## TYRES

|                 |                           |
|-----------------|---------------------------|
| Product group   | Tyres                     |
| Item number     | 15284350                  |
| Valid tyre size | 650 / 65 R 42             |
| LI / SI / PR    | 176 A8 / 171 D            |
| TL/TT           | TL                        |
| Brand           | Alliance                  |
| Tread pattern   | Multiuse Professional 551 |



## Notes and features

- The Alliance Multiuse Professional 551 is a new and recently developed tyre for use on municipal tractors, backhoe loaders and other agro-industrial machinery.
- Its additional sipes on the tread blocks ensure optimum handling, ride comfort and traction on dry, wet and snow-covered surfaces.
- The tyre is marked M+S and specially equipped for winter use.
- Due to the unique combination of special rubber compound and tread pattern design, the tyre guarantees excellent performance and a long service life.
- The strong steel-belted casing provides damage protection and optimum stability.

## Technical Informations

|                              |                           |
|------------------------------|---------------------------|
| Item number                  | 15284350                  |
| EAN                          | 7291050083140             |
| Valid tyre size              | 650 / 65 R 42             |
| LI / SI / PR                 | 176 A8 / 171 D            |
| TL/TT                        | TL                        |
| Brand                        | Alliance                  |
| Tread pattern                | Multiuse Professional 551 |
| M+S                          | M+S                       |
| Carcass properties           | Steel Belted              |
| Antistatic                   | No                        |
| Tyre colour                  | Black                     |
| ECE regulation number        | ECE 106                   |
| Nettogewicht [kg] (gültig)   | 238,60                    |
| Recommended rim size         | DW20B                     |
| Permitted rim size           | DW18L                     |
| Maximum air pressure [bar].  | 3,20                      |
| Section width (mm)           | 626                       |
| Outer diameter of tyre [mm]. | 1918                      |
| Stat. radius (SLR) [mm]      | 881                       |
| Rolling circumference [mm].  | 5779                      |
| Tread depth (mm)             | 31,0                      |
| Number of lugs               | 48x2                      |
| Tyre capacity 75% [ltr.]     | 715.5                     |
| E-Ready                      | No                        |

Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 176 A8 | 7100               | 40           |               | 3,20                     |              |
| 171 D  | 6150               | 65           |               | 3,20                     |              |