

TYRES

Product group	Tyres	
Item number	15284350	
Valid tyre size	650 / 65 R 42	
LI / SI / PR	176 A8 / 171 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multiuse Professional 551	



Notes and features

- The Alliance Multiuse Professional 551 is a new and recently developed tyre for use on municipal tractors, backhoe loaders and other agro-industrial machinery.
- Its additional sipes on the tread blocks ensure optimum handling, ride comfort and traction on dry, wet and snowcovered surfaces.
- The tyre is marked M+S and specially equipped for winter use
- Due to the unique combination of special rubber compound and tread pattern design, the tyre guarantees excellent performance and a long service life.
- The strong steel-belted casing provides damage protection and optimum stability.



Technical Informations

Item number	15284350
EAN	7291050083140
Valid tyre size	650 / 65 R 42
LI / SI / PR	176 A8 / 171 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse Professional 551
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	238,60
Recommended rim size	DW20B
Permitted rim size	DW18L
Maximum air pressure [bar].	3,20
Section width (mm)	626
Outer diameter of tyre [mm].	1918
Stat. radius (SLR) [mm]	881
Rolling circumference [mm].	5779
Tread depth (mm)	31,0
Number of lugs	48x2
Tyre capacity 75% [ltr.]	715.5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		3,20	
171 D	6150	65		3,20	