

## TYRES

Product group	Tyres
Item number	15284925
Valid tyre size	455 / 70 R 20
LI / SI / PR	162 A2 / 150 B
TL/TT	TL
Brand	Alliance
Tread pattern	608



## Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- High lugs in the shoulder area for traction on loose surfaces.
- Optimised rolling resistance allows fuel savings.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.

## Technical Informations

Item number	15284925
EAN	7291050062282
Valid tyre size	455 / 70 R 20
LI / SI / PR	162 A2 / 150 B
TL/TT	TL
Brand	Alliance
Tread pattern	608
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	73,54
Recommended rim size	14
Maximum air pressure [bar].	3,75
Section width (mm)	445
Outer diameter of tyre [mm].	1146
Stat. radius (SLR) [mm]	518
Rolling circumference [mm].	3465
Tread depth (mm)	20,0
Number of lugs	23x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A2	4750	10		3,75	
150 B	3350	50		3,75	