

TYRES

Product group	Tyres
Item number	15285290
Valid tyre size	425 / 75 R 20
LI / SI / PR	154 A8 / 154 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Technical Informations

Item number	15285290
EAN	7291050060585
Valid tyre size	425 / 75 R 20
Alternative size 1	16.5R20
LI / SI / PR	154 A8 / 154 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	81,28
Recommended rim size	13
Permitted rim size	11, 12, 14
Maximum air pressure [bar].	4,00
Section width (mm)	420
Outer diameter of tyre [mm].	1138
Stat. radius (SLR) [mm]	511
Rolling circumference [mm].	3449
Tread depth (mm)	33,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40		4,00	
154 B	3750	50		4,00	