

TYRES

| | |
|-----------------|---------------------|
| Product group | Tyres |
| Item number | 15285330 |
| Valid tyre size | 440 / 80 R 24 |
| LI / SI / PR | 161 A8 / 161 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agro Industrial 580 |



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Technical Informations

| | |
|------------------------------|---------------------|
| Item number | 15285330 |
| EAN | 7291050050371 |
| Valid tyre size | 440 / 80 R 24 |
| Alternative size 1 | 16.9R24 |
| LI / SI / PR | 161 A8 / 161 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agro Industrial 580 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 113,43 |
| Recommended rim size | 14 |
| Permitted rim size | 15 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 449 |
| Outer diameter of tyre [mm]. | 1309 |
| Stat. radius (SLR) [mm] | 591 |
| Rolling circumference [mm]. | 3865 |
| Tread depth (mm) | 40,0 |
| Number of lugs | 20x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 161 A8 | 4625 | 40 | | 4,00 | |
| 161 B | 4625 | 50 | | 4,00 | |