

## TYRES

Product group	Tyres
Item number	15285380
Valid tyre size	305 / 70 R 16.5
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



## Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

## Technical Informations

Item number	15285380
EAN	8903635048220
Valid tyre size	305 / 70 R 16.5
Alternative size 1	12R16.5
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	37,10
Recommended rim size	9.75
Maximum air pressure [bar].	4,00
Section width (mm)	307
Outer diameter of tyre [mm].	831
Stat. radius (SLR) [mm]	377
Rolling circumference [mm].	2466
Tread depth (mm)	23,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	57.3
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40		4,00	
132 B	2000	50		1,60	