

TYRES

| | |
|-----------------|---------------------|
| Product group | Tyres |
| Item number | 15710431 |
| Valid tyre size | 20 x 10.00 - 10 |
| LI / SI / PR | 94 A3 / 90 A6, 6 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | LG 306 |



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).

Technical Informations

| | |
|------------------------------|---------------------|
| Item number | 15710431 |
| EAN | 8903094012459 |
| Valid tyre size | 20 x 10.00 - 10 |
| LI / SI / PR | 94 A3 / 90 A6, 6 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | LG 306 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 6,94 |
| Recommended rim size | 8.00 |
| Maximum air pressure [bar]. | 2,20 |
| Section width (mm) | 250 |
| Outer diameter of tyre [mm]. | 508 |
| Stat. radius (SLR) [mm] | 226 |
| Rolling circumference [mm]. | 1473 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 94 A3 | 670 | 15 | | 2,20 | |
| 90 A6 | 600 | 30 | | 2,20 | |