

TYRES

Product group	Tyres
Item number	15726290
Valid tyre size	320 / 85 R 34
LI / SI / PR	141 A8 / 141 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Notes and features

- Standard tyre of the 85 series for tractors in the mediumpower range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.

- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

Item number	15726290
EAN	8903094040414
Valid tyre size	320 / 85 R 34
Alternative size 1	12.4R34
LI / SI / PR	141 A8 / 141 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	76,00
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	3,60
Section width (mm)	329
Outer diameter of tyre [mm].	1408
Stat. radius (SLR) [mm]	645
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4280
Tread depth (mm)	42,0
Tyre capacity 75% [ltr.]	149
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40		3,60	
141 B	2575	50		3,60	