

TYRES

Product group	Tyres
Item number	15726433
Valid tyre size	520 / 85 R 42
LI / SI / PR	168 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

Item number	15726433
EAN	8903094044634
Valid tyre size	520 / 85 R 42
LI / SI / PR	168 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	232,56
Recommended rim size	DW16L
Permitted rim size	W15L, DW15L, DD16L, W16L, DD18L, DW18L, W18L
Maximum air pressure [bar].	3,20
Section width (mm)	516
Tread width (mm)	480
Outer diameter of tyre [mm].	1951
Stat. radius (SLR) [mm]	890
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5851
Tread depth (mm)	57,0
Number of lugs	22x2
Tyre capacity 75% [litr.]	545.85
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		3,20	