

TYRES

Product group	Tyres
Item number	15726458
Valid tyre size	420 / 80 R 46
LI / SI / PR	170 A2 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726458
EAN	8903094046072
Valid tyre size	420 / 80 R 46
Alternative size 1	16.9R46
LI / SI / PR	170 A2 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	159,93
Recommended rim size	W13
Permitted rim size	W12
Maximum air pressure [bar].	3,20
Section width (mm)	418
Outer diameter of tyre [mm].	1840
Stat. radius (SLR) [mm]	863
Speed Radius Index (SRI)	900
Rolling circumference [mm].	5641
Tread depth (mm)	51,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	371.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A2	6000	10		3,20	
159 D	4375	65		3,20	