

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 15726658 |
| Valid tyre size | 620 / 75 R 26 |
| LI / SI / PR | 167 A8 / 167 B |
| TL/TT | TL |
| Brand | ВКТ |
| Tread pattern | Agrimax RT 600 |





Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.



Technical Informations

| Item number | 15726658 |
|------------------------------|----------------|
| EAN | 8903094050444 |
| Valid tyre size | 620 / 75 R 26 |
| Alternative size 1 | 23.1R26 |
| LI / SI / PR | 167 A8 / 167 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 600 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 177,00 |
| Recommended rim size | DW20B |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 625 |
| Tread width (mm) | 560 |
| Outer diameter of tyre [mm]. | 1590 |
| Stat. radius (SLR) [mm] | 730 |
| Speed Radius Index (SRI) | 750 |
| Rolling circumference [mm]. | 4851 |
| Tread depth (mm) | 45,0 |
| Number of lugs | 21x2 |
| Tyre capacity 75% [ltr.] | 567.75 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 167 A8 | 5450 | 40 | | 3,20 | |
| 167 B | 5450 | 50 | | 3,20 | |