

TYRES

Product group	Tyres
Item number	15727134
Valid tyre size	IF 680 / 85 R 32 CFO
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

Technical Informations

Item number	15727134
EAN	8903094065486
Valid tyre size	IF 680 / 85 R 32 CFO
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	288,00
Recommended rim size	DW23B
Permitted rim size	DW21B
Maximum air pressure [bar].	2,40
Section width (mm)	682
Tread width (mm)	615
Outer diameter of tyre [mm].	1960
Stat. radius (SLR) [mm]	846
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5860
Tread depth (mm)	46,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		2,40	