

## TYRES

Product group	Tyres
Item number	15727300
Valid tyre size	1050 / 50 R 32 CHO
LI / SI / PR	184 A8 / 181 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris



## Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

## Technical Informations

Item number	15727300
EAN	8903094032723
Valid tyre size	1050 / 50 R 32 CHO
LI / SI / PR	184 A8 / 181 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	462,88
Recommended rim size	36.0VA
Maximum air pressure [bar].	3,20
Section width (mm)	1059
Tread width (mm)	980
Outer diameter of tyre [mm].	1893
Stat. radius (SLR) [mm]	840
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5685
Tread depth (mm)	60,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A8	9000	40		3,20	
181 B	8250	50		3,20	