

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15727305 |
| Valid tyre size | 1050 / 50 R 32 |
| LI / SI / PR | 184 A8 / 181 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 600 |



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
 - Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
 - Large footprint enables excellent flotation properties.
 - Reinforced bead provides high load capacity.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15727305 |
| EAN | 8903094040728 |
| Valid tyre size | 1050 / 50 R 32 |
| LI / SI / PR | 184 A8 / 181 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 600 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 426,06 |
| Recommended rim size | 36.0VA mtlg. |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 1059 |
| Tread width (mm) | 980 |
| Outer diameter of tyre [mm]. | 1863 |
| Stat. radius (SLR) [mm] | 826 |
| Speed Radius Index (SRI) | 875 |
| Rolling circumference [mm]. | 5700 |
| Tread depth (mm) | 46,5 |
| Number of lugs | 21x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 184 A8 | 9000 | 40 | | 3,20 | |
| 181 B | 8250 | 50 | | 3,20 | |