

TYRES

Product group	Tyres
Item number	15727477
Valid tyre size	230 / 95 R 40
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727477
EAN	8903094055210
Valid tyre size	230 / 95 R 40
Alternative size 1	9.5R40
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	54,14
Recommended rim size	W7
Permitted rim size	W8
Maximum air pressure [bar].	4,00
Section width (mm)	228
Outer diameter of tyre [mm].	1454
Stat. radius (SLR) [mm]	690
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4445
Tread depth (mm)	35,0
Number of lugs	31x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40		4,00	
132 B	2000	50		4,00	