

TYRES

Product group	Tyres
Item number	17415800
Valid tyre size	710 / 55 R 34
LI / SI / PR	177 D
TL/TT	TL
Brand	Nokian
Tread pattern	ELS



nokian®
TYRES

Notes and features

- The flotation radial tyre was specially designed for field applications, if field use clearly predominates over road use.
- Thanks to its high load capacity, it is especially suitable for heavy agricultural machines and trailers.
- In the SB versions, the tyre is extremely robust due to the steel belt.
- Particularly gentle on the soil due to its wide contact area, rounded shoulders and low tyre pressure. Also suitable for delicate green areas.
- Very good grip and steering characteristics on soft surfaces.

Technical Informations

Item number	17415800
EAN	6419440454702
Valid tyre size	710 / 55 R 34
LI / SI / PR	177 D
TL/TT	TL
Brand	Nokian
Tread pattern	ELS
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	197,57
Recommended rim size	DW24B
Permitted rim size	DW2020B, DW23B
Maximum air pressure [bar].	4,00
Section width (mm)	707
Outer diameter of tyre [mm].	1641
Stat. radius (SLR) [mm]	748
Dynamic radius [mm]	795
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4995
Tread depth (mm)	26,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 D	7300	65		4,00	