

## **TYRES**

Product group	Tyres	
Item number	17416050	
Valid tyre size	710 / 40 - 24.5	
LI / SI / PR	170 A2 / 163 A8, 20 PR	
TL/TT	тт	
Brand	Nokian	
Tread pattern	Forest King TRS 2	





## Notes and features

- Top-class innovation for forest construction sites with or without caterpillar tracks.
- The new shoulder construction improves the additional support for the bands and increases puncture resistance.
- Super Shovel lug design improves the traction.
- New bead area with high resistance against rim slipping.
- Wide tread for low pressure on the soil.



## **Technical Informations**

Item number	17416050
EAN	6419440455686
Valid tyre size	710 / 40 - 24.5
LI / SI / PR	170 A2 / 163 A8, 20 PR
TL/TT	ТТ
Brand	Nokian
Tread pattern	Forest King TRS 2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	188,73
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	710
Outer diameter of tyre [mm].	1230
Stat. radius (SLR) [mm]	570
Dynamic radius [mm]	598
Rolling circumference [mm].	3757
Tyre capacity 75% [ltr.]	380
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A2	6000	10		5,00	
163 A8	4875	40		5,00	