

TYRES

Product group	Tyres	
Item number	17426100	
Valid tyre size	300 / 80 R 24	
LI / SI / PR	133 A8 / 128 D	
TL/TT	TL	
Brand	Nokian	
Tread pattern	TRI 2	



nokian[®] TYRES

Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.
- Steel Belted.



Technical Informations

Item number	17426100
EAN	6419440454191
Valid tyre size	300 / 80 R 24
Alternative size 1	11.2R24
LI / SI / PR	133 A8 / 128 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	51,49
Recommended rim size	DW10
Permitted rim size	W9, W10, W11, DW11
Maximum air pressure [bar].	3,20
Section width (mm)	295
Outer diameter of tyre [mm].	1090
Stat. radius (SLR) [mm]	502
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3297
Tread depth (mm)	24,0
Tyre capacity 75% [ltr.]	97.5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		3,20	
128 D	1800	65		3,20	