# Bohnenkamp Moving Professionals

### **TYRES**

Product group	Tyres
Item number	17426195
Valid tyre size	460 / 65 R 24
LI / SI / PR	156 A8 / 151 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



#### Notes and features

- Ideal in the most varying conditions, reliable throughout . the whole year.
- High level of directional stability in on-road and off-road • applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability. .
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.
- Steel Belted. .

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

## **Technical Informations**

Item number	17426195	
EAN	6419440453934	
Valid tyre size	460 / 65 R 24	
LI / SI / PR	156 A8 / 151 D	
TL/TT	ть	
Brand	Nokian	
Tread pattern	TRI 2	
M+S	M+S	
TRA Code	R4	
Carcass properties	Steel Belted	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	not necessary	
Nettogewicht [kg] (gültig)	96,01	
Recommended rim size	DW14L	
Permitted rim size	W15L, W16L, DW15L, DW16L	
Maximum air pressure [bar].	4,00	
Section width (mm)	439	
Outer diameter of tyre [mm].	1204	
Stat. radius (SLR) [mm]	540	
Speed Radius Index (SRI)	575	
Rolling circumference [mm].	3644	
Tread depth (mm)	28,0	
Tyre capacity 75% [ltr.]	202.50	
E-Ready	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		4,00	
151 D	3450	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.