

TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 17426215       |
| Valid tyre size | 480 / 65 R 28  |
| LI / SI / PR    | 154 A8 / 149 D |
| TL/TT           | TL             |
| Brand           | Nokian         |
| Tread pattern   | TRI 2          |



Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
  - High level of directional stability in on-road and off-road applications.
  - The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
  - Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.
  - Steel Belted.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 17426215       |
| EAN                          | 6419440454443  |
| Valid tyre size              | 480 / 65 R 28  |
| LI / SI / PR                 | 154 A8 / 149 D |
| TL/TT                        | TL             |
| Brand                        | Nokian         |
| Tread pattern                | TRI 2          |
| M+S                          | M+S            |
| TRA Code                     | R4             |
| Carcass properties           | Steel Belted   |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 106,29         |
| Recommended rim size         | DW15L          |
| Permitted rim size           | DW14L, DW16L   |
| Maximum air pressure [bar].  | 3,20           |
| Section width (mm)           | 464            |
| Outer diameter of tyre [mm]. | 1336           |
| Stat. radius (SLR) [mm]      | 604            |
| Dynamic radius [mm]          | 641            |
| Speed Radius Index (SRI)     | 650            |
| Rolling circumference [mm].  | 4025           |
| Tread depth (mm)             | 28,0           |
| Tyre capacity 75% [ltr.]     | 259.00         |
| E-Ready                      | No             |

Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 154 A8 | 3750               | 40           |               | 3,20                     |              |
| 149 D  | 3250               | 65           |               | 3,20                     |              |