

TYRES

Product group	Tyres	
Item number	17426950	
Valid tyre size	650 / 65 R 42	
LI / SI / PR	176 A8 / 171 D	
TL/TT	TL	
Brand	Nokian	
Tread pattern	TRI 2	





Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.
- Steel Belted.



Technical Informations

Item number	17426950
EAN	6419440453903
Valid tyre size	650 / 65 R 42
Alternative size 1	20.8R42
LI / SI / PR	176 A8 / 171 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	269,01
Recommended rim size	DW20A
Permitted rim size	DW18L, DW23A
Maximum air pressure [bar].	3,20
Section width (mm)	617
Outer diameter of tyre [mm].	1913
Stat. radius (SLR) [mm]	848
Dynamic radius [mm]	922
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5791
Tread depth (mm)	33,0
Tyre capacity 75% [ltr.]	693.75

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		3,20	
171 D	6150	65		3,20	