Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	17427226
Valid tyre size	460 / 70 R 24
LI / SI / PR	161 D
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta TRI





Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces. Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in • contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.
- Steel Belted.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17427226
EAN	6419440349664
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	161 D
TL/TT	тι
Brand	Nokian
Tread pattern	Hakkapeliitta TRI
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	118,70
Recommended rim size	DW14L
Permitted rim size	DW15L
Maximum air pressure [bar].	5,00
Section width (mm)	460
Outer diameter of tyre [mm].	1255
Stat. radius (SLR) [mm]	557
Rolling circumference [mm].	3792
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	218
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 D	4625	65		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.