

## **TYRES**

Product group	Tyres	
Item number	17427228	
Valid tyre size	500 / 70 R 24	
LI / SI / PR	166 D	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Hakkapeliitta TRI	





## Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces.
  Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.
- Steel Belted.



## **Technical Informations**

Item number	17427228
EAN	6419440349633
Valid tyre size	500 / 70 R 24
Alternative size 1	19.5LR24
LI / SI / PR	166 D
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta TRI
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	133.77
Recommended rim size	DW16L
Maximum air pressure [bar].	5,00
Section width (mm)	500
Outer diameter of tyre [mm].	1314
Stat. radius (SLR) [mm]	580
Rolling circumference [mm].	3971
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	278
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		5,00	