

## **TYRES**

Product group	Tyres
Item number	18545017
Valid tyre size	155 / 70 R 12 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	BK Trailer
Tread pattern	204



## Notes and features

- Reinforced sidewall design.
- The special flat tread design for trailer & caravan use ensures optimum running smoothness and driving stability.
- Low abrasion due to a special rubber compound.
- Increased payload.



## **Technical Informations**

Item number	18545017
EAN	4040658078743
Valid tyre size	155 / 70 R 12 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	BK Trailer
Tread pattern	204
M+S	M+S
Rolling resistance	D
Wet grip	D
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	5,90
Recommended rim size	4.50J
Permitted rim size	4.00B, 4J, 4.50B, 5.00B, 5J
Maximum air pressure [bar].	6,50
Section width (mm)	157
Outer diameter of tyre [mm].	523
Stat. radius (SLR) [mm]	240
Rolling circumference [mm].	1585
Tread depth (mm)	6,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 N	900	140	Single	6,50	
102 N	850	140	Twin	6,50	